

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113467 A1

(51) International Patent Classification⁷: C09K 7/06

(21) International Application Number:
PCT/GB2004/001950

(22) International Filing Date: 6 May 2004 (06.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/464,238 18 June 2003 (18.06.2003) US

(71) Applicant (for all designated States except US): HAL-
LIBURTON ENERGY SERVICES, INC. [US/US]; P.O.
Box 1431, Duncan, OK 73533 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): TEMPLE, Colin
[GB/GB]; Brooklands, Hattoncrook, Aberdeenshire AB51
0QQ (GB). PATERSON, Andrew, Forbes [GB/GB]; 25
Glebe Park, Banchory, Aberdeenshire AB31 5YT (GB).
LEITH, Christopher, Duncan [GB/GB]; Springwood
Lodge, Tillyvee, Udney, Aberdeenshire AB41 6SJ (GB).

(74) Agents: WAIN, Christopher, Paul et al.; A A Thornton
& Co, 235 High Holbon, London WC1V 7LE (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR REDUCING SAG IN DRILLING, COMPLETION AND WORKOVER FLUIDS

(57) Abstract: A method is disclosed for reducing sag in drilling and completion fluids and in workover fluids. The method employs a drilling fluid comprising a low molecular weight polyalkyl methacrylate with an average molecular weight ranging from about 40,000 to about 90,000. This additive does not result in enhanced viscosity of the fluid.

WO 2004/113467 A1

METHOD FOR REDUCING SAG IN DRILLING, COMPLETION AND WORKOVER FLUIDS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to methods and compositions for reducing the sag of a weight material in a drilling fluid for drilling operations such as drilling, running casing, and cementing and in fluids for workover operations.

2. Description of Relevant Art

A drilling fluid, or "mud" which a drilling fluid is also often called, is a specially designed fluid that is circulated in a wellbore or borehole as the wellbore is being drilled in a subterranean formation to facilitate the drilling operation. As used herein, the term "drilling operation" shall mean drilling, running casing and/or cementing unless indicated otherwise. The various functions of a drilling fluid include removing drill cuttings from the wellbore, cooling and lubricating the drill bit, aiding in support of the drill pipe and drill bit, and providing a hydrostatic head to maintain the integrity of the wellbore walls and prevent well blowouts. Specific drilling fluid systems are selected to optimize a drilling operation in accordance with the characteristics of a particular geological formation.

A drilling fluid typically comprises water and/or oil or synthetic oil or other synthetic material or synthetic fluid as a base fluid, with solids in suspension. A non-aqueous based drilling fluid typically contains oil or synthetic fluid as a continuous phase and may also contain water dispersed in the continuous phase by emulsification so that there is no distinct layer of water in the fluid. Such dispersed water in oil is generally referred to as an invert emulsion or water-in-oil emulsion.

A number of additives may be included in such drilling fluids and invert emulsions to enhance certain properties of the fluid. Such additives may include, for example, emulsifiers, weighting agents, fluid-loss additives or fluid-loss control agents, viscosifiers or viscosity control agents, and alkali. Weighting agents are commonly added to increase the density of the fluid. Barite or barytes (barium sulphates) are typical weighting agents, although other minerals are also common.

Viscosifiers are typically added to increase the viscosity of the fluid to facilitate or enhance suspension of weighting agents in the fluid. Organoclays, such as for example

bentonites hectorites and other swelling clays, chemically treated to enhance their oil wettability, are typical viscosifiers. Organic polymers and long chain fatty acids may also be added to increase viscosity and aid weighting agent suspension.

Generally, increased viscosity leads to improved suspension of weighting agents which in turn limits or reduces problematic "sag." However, excessive viscosity can have adverse effects on equivalent circulating density (causing it to increase), which can also lead to problems, particularly in wells where the differences in subterranean formation pore pressures and fracture gradients are small, as commonly encountered in deep water wells.

Under certain well conditions, including without limitation, well geometries, temperatures and pressures, a phenomenon called "barite sag" or "sag" can occur. "Sag" is generally a "significant" variation in mud density (> 0.5 lbm/gal) along the mud column, which is the result of settling of the weighting agent or weight material and other solids in the drilling fluid. Sag generally results from the inability of the drilling fluid under the particular well conditions to provide adequate suspension properties.

Suspensions of solids in non-vertical columns are known to settle faster than suspensions in vertical ones. This effect is driven by gravity and impeded by fluid rheology, particularly non-Newtonian and time dependent rheology. Manifestation of this effect in a drilling fluid is also known as "sag," although sag occurs in both vertical and non-vertical wells.

Drilling fluids in deviated wellbores can exhibit sag in both static and dynamic situations. In this context, static is a totally quiescent fluid state, such as when drilling has ceased; dynamic is any situation where the fluid is exposed to a shear stress, such as for example during drilling. As used hereinafter, the term "sag" shall be understood to include both static and dynamic sag unless specifically indicated otherwise.

Sag can result in formation of a bed of the weighting agents on the low side of the wellbore, and stuck pipe, among other things. In some cases, sag can be very problematic to the drilling operation and in extreme cases may cause hole abandonment. As directional drilling and deviated wellbores become more common if not the norm in the oil and gas industry, more and improved methods are needed to reduce or eliminate sag, without adding viscosity problems.

SUMMARY OF THE INVENTION

The present invention provides a method for reducing sag or the settlement of weighting agents in an oil based or invert emulsion drilling fluid without significantly increasing the viscosity of the drilling fluid. The method comprises adding a low molecular weight polyalkyl methacrylate to the drilling fluid. No copolymer such as vinyl pyrrolidone or its equivalent is needed or used. The invention also provides a drilling fluid comprising the additive. As used herein, the term "drilling fluid" shall be understood to include fluids used in drilling, cementing, casing, workover and/or other similar downhole operations.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

In the present invention, an oil or invert emulsion based drilling fluid comprising a low molecular weight polyalkyl methacrylate additive is used in drilling operations or workover operations. The fluid provides good suspension of weighting agents without excessive viscosity and shows a reduced rate of sag when compared to prior art fluids.

The effective average molecular weight range of the polyalkyl methacrylate is about 40,000 to about 90,000. A polyalkyl methacrylate within this weight range is commercially available under the tradename VISCOPLEX® 1-304, available from ROHMAX or Rohm GmbH of Germany. Preferred concentrations of this additive in the drilling fluid are in the range of about 0.5 ppb to about 10 ppb. At these concentrations, this additive of the present invention does not significantly increase the viscosity of the drilling fluid when measured at either about 120 degrees Fahrenheit and ambient pressure or at temperatures up to about 400 degrees Fahrenheit and 20,000 psig pressure.

Sag factors achieved using this low molecular weight polyalkyl methacrylate additive range from about 0.50 to about 0.51. Typical prior art drilling fluids presently in use in the oil and gas industry exhibit sag factors ranging from about 0.51 to about 0.55, where a sag factor of 0.50 indicates no settlement of weighting agent (i.e., no sag). Copolymers with the polyalkyl methacrylate are not needed in the present invention.

United States Patent No. 6,204,224, issued March 20, 2001 to Quintero et al. previously reported use of a copolymer of a high molecular weight polyalkyl methacrylate and vinyl pyrrolidone for rheological modification and filtration control for oil or invert emulsion based, and particularly ester and synthetic based, drilling fluids. These copolymers

are said to be capable of building a viscoelastic rheological structure which serves to prevent or reduce barite sag and provide cuttings transport. The patent includes data comparing the copolymer of high molecular weight polyalkyl methacrylate and vinyl pyrrolidone with a copolymer of low molecular weight polyalkyl methacrylate and vinyl pyrrolidone which indicates that the latter yielded poor results in contrast to the claimed high molecular weight polyalkyl methacrylate and vinyl pyrrolidone copolymer. The data in the patent followed traditional expectations that the more viscous fluid would provide the better suspension properties and be less likely to sag. Addition of the high molecular weight polyalkyl methacrylate and vinyl pyrrolidone copolymer to the drilling fluid significantly increased the viscosity of the fluid, which resulted in the drilling fluid being a highly viscous fluid.

Notwithstanding the teaching of U.S. Patent No. 6,204,224 to Quintero, et al., the present invention departs from traditional thinking and unexpectedly provides a formulation that yields superior results in reducing sag without added viscosity and thus without consequent problems that highly viscous fluids can cause. The advantages of the present invention are demonstrated by the test data below.

EXPERIMENTS

Initially, samples of field drilling mud were either static aged or hot rolled at 400 degrees Fahrenheit to evaluate the mud at 50 degrees Fahrenheit higher than the mud was originally engineered to withstand. The mud generally held up well, although the difference between the top and bottom density results were excessive. To improve barite (weighting agent) suspension, two different products were added to samples (one product per sample) for comparison in concentrations of 1.0 lb/bb. These two products were castor oil and VISCOPLEX® 1-304. Data from this experiment is shown in Table 1 below.

TABLE 1

Field Mud Sample	bbl	1.0		1.0	1.0
Hydrogenated Castor Oil	lb	---		1.0	---
VISCOPLEX®1-304	lb	---		---	1.0
Static Aged @ 400 °F	hour		16	16	16
Plastic Viscosity	cP	58	75	80	74
Yield Point	lb/100ft ²	22	29	23	27
10 second Gel	lb/100ft ²	14	24	20	24
10 minute Gel	lb/100ft ²	19	40	38	37
<i>Fann 35 dial readings @ 120°F</i>					
⊙ 600		138	179	183	175
⊙ 300		80	104	103	101
⊙ 200		60	77	76	74
⊙ 100		38	48	46	48
⊙ 6		13	16	14	16
⊙ 3		10	14	12	14
Weight	lb/gal		18.0	18.0	18.0
Top Oil Separation	%		3.0	3.0	2.5
Gelled/Settling	y/n		y/n	y/n	y/n
Top Stratification	sg		1.87	2.05	2.10
Middle Stratification	sg		2.10	2.21	2.17
Bottom Stratification	sg		2.29	2.32	2.22

The concentration of each additive--the castor oil and the VISCOPLEX® 1-304--was increased in additional samples of field mud to 2.0 lb/bbl. As the data in Table 2 indicates, this addition had the desired effect of reducing settlement (e.g., sag) during static aging without adverse effects on (i.e., without increasing) either viscosity or fluid loss. Of these two additives, the better results were seen with VISCOPLEX® 1-304 and so the remaining studies were conducted only with VISCOPLEX® 1-304.

TABLE 2

Field Mud Sample	bbl	1.0	1.0	1.0
Hydrogenated Castor Wax	lb	---	2.0	---
VISCOPLEX®1-304	lb	---	---	2.0
Static Aged @ 400 °F	hour	16	16	16
Plastic Viscosity	cP	54	60	75
Yield Point	lb/100ft ²	22	27	35
10 second Gel	lb/100ft ²	13	17	21
10 minute Gel	lb/100ft ²	18	42	49
Electrical Stability	volt	---	654	776
HTHP Fluid Loss @ 400°F	ml/30min	---	---	2.2
<i>Fann 35 dial readings @ 120°F</i>				
⊙ 600		130	147	185
⊙ 300		76	87	110
⊙ 200		57	65	83
⊙ 100		36	42	53
⊙ 6		12	14	17
⊙ 3		10	12	15
Weight	lb/gal	18.0	18.0	18.0
Top Oil Separation	%	2.5	2.5	1.5
Gelled/Settling	y/n	y/n	y/n	y/n
Top Stratification	sg	1.94	2.01	2.12
Middle Stratification	sg	2.12	2.16	2.19
Bottom Stratification	sg	2.29	2.29	2.24

Laboratory samples of a drilling mud approximately like the field mud were prepared. Different concentrations of VISCOPLEX® 1-304 was added to the samples—1.0 lb/bbl concentration in one sample and 2.0 lb/bbl concentration in another sample. These samples were static aged at 400 degrees Fahrenheit for 16 hours. The treated laboratory samples showed low density variations and minimal top oil separation, with the 2.0 lb/bbl concentration giving slightly better results. The data from this experiment is shown in Table 3 below. The products in the tables designated by tradenames EZ MUL® NT, INVERMUL® NT, DURATONE®, BENTONE®, and SUSPENTONE™ are available from Halliburton Energy Services, Inc. in Houston, Texas, U.S.A. These products are common additives for

completing a drilling fluid and comprise emulsifiers, rheological control additives, suspension agents and the like.

TABLE 3

MUD SAMPLE COMPOSITION						
Total DF 1 (invert emulsion base)	bbl	0.393			0.393	0.393
EZ MUL® NT	ppb	15.0			15.0	15.0
INVERMUL® NT	ppb	3.0			3.0	3.0
DURATONE® HT	ppb	20.0			20.0	20.0
Lime	ppb	10.0			10.0	10.0
BENTONE® 38	ppb	2.0			2.0	2.0
Water	bbl	0.102			0.102	0.102
CaCl ₂		19.01			19.01	19.01
ppb						
SUSPENTONE™		2.0			2.0	2.0
ppb						
Barite	ppb	559.93			559.9	559.93
RM™ 63		1.0			1.0	1.0
ppb						
VISCOPLEX® 1-304	ppb	---			1.0	2.0
Static Aged @ 400°F	hour		16		16	16
MUD SAMPLE PROPERTIES						
Plastic Viscosity	cP	65	62	60	62	61
Yield Point	lb/100ft ²	25	19	23	16	17
10 second Gel	lb/100ft ²	15	12	15	10	14
10 minute Gel	lb/100ft ²	26	31	20	30	32
Fann 35 dial readings @ 120°F						
⊙ 600		155	143	143	140	139
⊙ 300		90	81	83	78	78
⊙ 200		68	59	62	57	57
⊙ 100		44	36	38	34	35
⊙ 6		15	10	12	8	9
⊙ 3		13	9	10	7	7
Weight	lb/gal		18.0		18.0	18.0
Top Oil Separation	%		3.5		2.5	2.0
Gelled/Settling	y/n		y/n		y/n	y/n
Top Stratification	sg		2.11		2.16	2.15
Middle Stratification	sg		2.22		2.18	2.17
Bottom Stratification	sg		2.36		2.22	2.20

One sample of the laboratory mud without the VISCOPLEX® 1-304 additive and one sample of the laboratory mud with 2.0 lb/bbl VISCOPLEX® 1-304 were placed in hot roll cells and left static in an oven for 96 hours at 400 degrees Fahrenheit. Though there was top oil separation and settlement in both cells, the sample with the VISCOPLEX® 1-304 showed significantly better results, as can be seen in Table 4.

TABLE 4

<i>MUD SAMPLE COMPOSITION:</i>			
Total DF 1 (invert emulsion base)	bbl	0.393	0.393
EZ MUL® NT		15.0	15.0
ppb			
INVERMUL® NT		3.0	3.0
ppb			
DURATONE® HT		20.0	20.0
ppb			
Lime	ppb	10.0	10.0
Bentone 38	ppb	2.0	2.0
Water	bbl	0.102	0.102
CaCl ₂		19.01	19.01
ppb			
SUSPENTONE	ppb	2.0	2.0
Barite	ppb	559.93	559.93
RM 63	ppb	1.0	1.0
VISCOPLEX® 1-304	ppb	---	2.0
Static Aged @ 400°F	hour	96	96
<i>MUD SAMPLE PROPERTIES</i>			
Plastic Viscosity	cP	60	63
Yield Point	lb/100ft ²	23	13
10 second Gel	lb/100ft ²	15	13
10 minute Gel	lb/100ft ²	20	32
Electrical Stability	volt	---	799
<i>Fann 35 dial readings @ 120°F</i>			
⊙ 600		143	139
⊙ 300		83	76
⊙ 200		62	54
⊙ 100		38	30
⊙ 6		12	7
⊙ 3		10	5
Weight	lb/gal	18.0	18.0
Top Oil Separation	%	20.0	15.0
Gelled/Settling	y/n	y/n	y/n

Top Stratification	sg		1.84	2.0
Middle Stratification	sg		2.36	2.20
Bottom Stratification	sg		2.70	2.50

A sample of the field mud sample without VISCOPLEX® and a sample of the field mud sample with 2.0 lb/bbl VISCOPLEX® 1-304 were sheared on a Silverson mixer over a 60 minute period before being static aged at 400 degrees Fahrenheit for 16 hours. The results, shown in Table 5, indicated no significant difference between the two samples, which indicated that VISCOPLEX™ can withstand shear.

TABLE 5

Field Mud Sample			
Sheared for 1 hour	bbl	1.0	---
VISCOPLEX®1-304	ppb	---	2.0
Static Aged @ 400°F	hour	16	16
Plastic Viscosity	cP	70	70
Yield Point	lb/100ft ²	27	28
10 second Gel	lb/100ft ²	22	26
10 minute Gel	lb/100ft ²	39	41
Electrical Stability	volt	838	1013
<i>Fann 35 dial readings @ 120°F</i>			
⊙ 600		167	168
⊙ 300		97	98
⊙ 200		72	73
⊙ 100		44	47
⊙ 6		14	17
⊙ 3		12	15
Weight	lb/gal	18.0	18.0
Top Oil Separation	%	3.5	2.5
Gelled/Settling	y/n	y/n	y/n
Top Stratification	sg	2.10	2.12
Middle Stratification	sg	2.18	2.14
Bottom Stratification	sg	2.22	2.17

Fann 70 rheological profiles were carried out on samples of both field mud without VISCOPLEX® 1-304 and field mud with 2.0 lb/bbl VISCOPLEX® 1-304. After the samples

reached the maximum temperatures and pressures desired, the samples were left for 4.5 hours at these maximum temperatures and pressures before instrument readings were re-taken. In addition to the Fann 70, the viscosity of both samples was measured on a Fann 35 at 5 degrees Centigrade to simulate cold climates. These tests showed no detrimental effects from the addition of VISCOPLEX® 1-304. The test data is reported in Tables 6 and 7 below.

TABLE 6
FANN 70 RHEOLOGICAL PROFILE
Field Mud Sample

Temperature (°C):	50	100	150	204	204	-5
Pressure (psi):	0	5000	11000	17500	17500	Fann 35
					4.5 Hours	
600 rpm	132	107	102	118	103	O/S
300 rpm	75	64	61	72	53	O/S
200 rpm	57	50	48	55	37	249
100 rpm	38	36	34	37	21	148
60 rpm	28	28	27	28	16	---
30 rpm	22	22	22	22	10	---
6	13	15	15	13	5	35
3	11	13	13	10	3	29
Plastic Viscosity, cp	57	43	41	46	50	---
Yield Point, lb/100ft ²	18	21	20	26	3	---
Gel, 10 sec. lb/100ft	12	13	13	10	3	37
Gel, 10 min. lb/100ft	15	16	15	13	6	61

TABLE 7
FANN 70 RHEOLOGICAL PROFILE
 Field Mud Sample + 2lb/bbl VISCOPLEX® 1-304

Temperature (°C):	50	100	150	204	204	-5
Pressure (psi):	0	5000	11000	17500	17500	Fann 35
					4.5 Hours	
600 rpm	144	123	96	99	97	O/S
300 rpm	84	79	63	60	52	O/S
200 rpm	65	64	52	47	39	253
100 rpm	44	47	39	34	23	152
60 rpm	34	39	32	25	17	---
30 rpm	25	31	26	21	11	---
6	16	22	19	14	6	36
3	14	21	17	11	3	30
Plastic Viscosity, cp	60	44	33	29	45	---
Yield Point, lb/100ft ²	24	35	30	31	7	---
Gel, 10 sec. lb/100ft	14	21	17	11	3	37
Gel, 10 min. lb/100ft	16	23	19	14	6	63

Several apparatus and procedures are available for measuring sag. A typical example is stratification testing to determine or evaluate the "sag" performance of a drilling fluid, i.e., the fluid's tendency to "sag." The procedure used in stratification testing is as follows:

A sample of the fluid or formulation is sealed within a stainless steel cell and placed vertically in an oven maintained at the expected maximum temperature of the well. The cell is usually pressurized using nitrogen to prevent loss of volatiles from the fluid. After the test period, typically 16 hours, the cell is depressurized and the volume of "top" (i.e., separated) oil is measured and expressed as a percentage of the total fluid volume. After removal of the top oil, the density of the fluid is measured at three depths—top, middle, and bottom. A "sag factor" is calculated by dividing the bottom density by the sum of the top and bottom densities. A sag factor of 0.5 indicates no settlement of weighting agents.

Stratification data is reported for sag calculations in Tables 1-5 above. As previously noted, the sag factors for the fluid tested with VISCOPLEX® 1-304 ranged from about 0.50

to about 0.51, generally indicating that sag either did not occur or did not occur in an appreciable or significant amount.

The viscosity of drilling fluid is typically measured by use of concentric cylinder viscometers such as the Fann 35, available from Fann Instruments in Houston, Texas, U.S.A. The viscosity of fluids under downhole conditions, i.e., temperatures up to about 500 degrees Fahrenheit and pressures to 20,000 psig, is typically measured using an instrument such as the Fann 70, available from Fann Instruments in Houston, Texas, U.S.A. Viscosity data is reported in all of the tables above and comparison of the viscosities of the fluids with and without VISCOPLEX® 1-304 indicates that the addition of VISCOPLEX® 1-304 to the fluid did not appreciably or significantly alter the viscosity of the fluid.

These experiments indicate that a low molecular weight polyalkyl methacrylate may be added to oil or invert emulsion based drilling fluids to obtain improved suspension properties or reduced sag without altering the viscosity of the fluid. Further, this additive does not seem to significantly alter or increase the fluid loss experienced with use of the fluid and the additive provides a further benefit of improving the static age results seen with the fluid.

The foregoing description of the invention is intended to be a description of preferred embodiments. Various changes in the details of the described drilling fluid and method can be made without departing from the intended scope of this invention as defined by the appended claims.

We claim:

1. A method for reducing sag in an oil or invert emulsion based drilling fluid, said method comprising adding to said fluid a low molecular weight polyalkyl methacrylate.
2. The method of claim 1 wherein the polyalkyl methacrylate has an average molecular weight ranging from about 40,000 to about 90,000.
3. The method of claim 1 wherein said fluid has a sag factor in the range of about 0.50 to about 0.51.
4. The method of claim 3 wherein said sag factor is determined according to stratification testing.
5. The method of claim 1 wherein the viscosity of said fluid before and after said addition of polyalkyl methacrylate is substantially the same.
6. The method of claim 1 wherein said polyalkyl methacrylate is provided in said fluid in a concentration ranging from about 0.5 ppb to about 10 ppb.
7. The method of claim 6 wherein said concentration of polyalkyl methacrylate ranges from about 1 ppb to about 2 ppb.
8. The method of claim 1 wherein said drilling fluid is used in drilling or completion operations.
9. The method of claim 1 wherein said drilling fluid is used in workover operations.
10. A drilling fluid comprising an oil or invert emulsion base, weighting agents and a low molecular weight polyalkyl methacrylate.
11. The drilling fluid of claim 10 wherein said polyalkyl methacrylate has an average molecular weight ranging from about 40,000 to about 90,000.
12. The drilling fluid of claim 10 wherein said polyalkyl methacrylate has a sag factor in the range of about 0.50 to about 0.51.
13. The drilling fluid of claim 10 wherein polyalkyl methacrylate is provided in said fluid in a concentration ranging from about 0.5 ppb to about 10 ppb. The drilling fluid of claim 13 wherein said concentration of polyalkyl methacrylate ranges from about 1 ppb to about 2 ppb.
14. The drilling fluid of claim 10 further comprising emulsifiers.

15. The drilling fluid of claim 14 further comprising at least one additive selected from the group comprising rheological additives, fluid loss control additives, and suspension agents.
16. A method for improving the suspension properties of an oil or invert emulsion based drilling fluid without significantly increasing the viscosity of said fluid, said method comprising adding to said fluid an additive comprising a low molecular weight polyalkyl methacrylate.
17. The method of claim 16 wherein said polyalkyl methacrylate is provided in a concentration ranging from about 0.5 ppb to about 10 ppb.
18. The method of claim 16 wherein said polyalkyl methacrylate has an average molecular weight ranging from about 40,000 to about 90,000.
19. The method of claim 16 wherein said fluid is used in drilling operations, completion operations, or workover operations in a borehole penetrating a subterranean formation.

INTERNATIONAL SEARCH REPORT

PCT/GB2004/001950

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C09K7/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, COMPENDEX

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,P	US 2004/002426 A1 (TEMPLE COLIN ET AL) 1 January 2004 (2004-01-01) the whole document	1-19
X	US 6 204 224 B1 (BRADFORD JR WILLIAM R ET AL) 20 March 2001 (2001-03-20) column 3 - column 4 examples 1-4	1-19
X	GB 2 342 671 A (BAKER HUGHES INC) 19 April 2000 (2000-04-19) page 3 - page 5; examples 1-4	1-19
A,P	US 6 586 372 B1 (BRADBURY ANDREW ET AL) 1 July 2003 (2003-07-01) the whole document	1-19
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

25 August 2004

Date of mailing of the international search report

01/09/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Zimpfer, E

INTERNATIONAL SEARCH REPORT

PCT/GB2004/001950

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 1 111 024 A (RHEOX INC) 27 June 2001 (2001-06-27) the whole document -----</p>	1-19

INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/GB2004/001950

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2004002426 A1	01-01-2004	WO 2004000968 A1 US 2003236172 A1	31-12-2003 25-12-2003
US 6204224 B1	20-03-2001	AU 747762 B2 AU 5399699 A GB 2342671 A , B NO 994974 A	23-05-2002 20-04-2000 19-04-2000 14-04-2000
GB 2342671 A	19-04-2000	AU 747762 B2 AU 5399699 A NO 994974 A US 6204224 B1	23-05-2002 20-04-2000 14-04-2000 20-03-2001
US 6586372 B1	01-07-2003	GB 2315505 A AU 3767697 A EP 0922078 A1 NO 990251 A WO 9803609 A1 US 2003203822 A1 US 2004127366 A1	04-02-1998 10-02-1998 16-06-1999 24-03-1999 29-01-1998 30-10-2003 01-07-2004
EP 1111024 A	27-06-2001	US 6339048 B1 CA 2322094 A1 EP 1111024 A1	15-01-2002 23-06-2001 27-06-2001